



RECOMMENDED
CABLE STRIPPING DIM'S
(建議剝線尺寸)

1. CONTACT PIN TO SOLDER
(中心針焊接)

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. PASSIVATED
 3. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
 4. TEFLON MIL-P-19468
 5. BERYLLIUM COPPER PER QQ-C-530
 6. STAINLESS STEEL PER QQ-S-764, TYPE 303

	CONTACT PIN	NOTE 1	NOTE 3		
	SHELL	NOTE 6	NOTE 2		
	C RING	NOTE 5	NONE		
	GASKET	SILICONE	RED		
	INSULATOR	NOTE 4	WHITE		
	BODY	NOTE 1	NOTE 3		
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

SMA-PC-405-LF
SERIES | LEADFREE
RG 405
CRIMP
MALE

DESCRIPTION:

SMA DIRECT SOLDER PLUG
(FOR SEMI-RIGID .085", SEMI-FLEXIBLE .085", SS405)