



尺寸公差	B	C	D	E	角度公差	±3°
1.0↓	±0.025	±0.05	±0.1	±0.25	Angular	±3°
1.0-2.0	±0.03	±0.06	±0.13	±0.3	Tolerance	
2.0-4.0	±0.04	±0.08	±0.16	±0.4		
4.0-8.0	±0.05	±0.1	±0.2	±0.5	100 ↓	±0.8
8.0-16	±0.06	±0.13	±0.25	±0.6		
16-31.5	±0.08	±0.16	±0.3	±0.8	50-100	±0.5
31.5-50	±0.1	±0.2	±0.4	±1.0		
50-125	±0.13	±0.25	±0.5	±1.25	5-50	±0.3
125-250	±0.16	±0.3	±0.6	±1.6		
250-500	±0.2	±0.4	±0.8	±2.0	5 ↓	±0.2
500↑	±0.25	±0.5	±1.0	±2.5		

### B.o.M

Item	Name	Spec.	QTY	Note.
1	SMA Plug R/A Connector	Au. Plate	2	
2	Heat Shrinking Sleeve	∅ 4x20	2	
3	Coaxial Cable	RG-188	1	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4

PPOJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

照片框

### ORDER INFORMATION

SMA2-1R1R188-M4N5-LF  
SERIES | LEADFREE  
115mm  
MALE TO MALE  
Rg188  
RT/RT

DESCRIPTION: SMA PLUG FOR RG-174 CABLE