



8	胶芯	T-09104T002-W	铁弗龙	白色	1
7	旋转头	B-09104B004-G	黄铜	金 AUF	1
6	PIN针	C-D9104B001-G	黄铜	金 AUF	1
5	铜管	F-D7801B004-G	黄铜	金 AUF	1
4	螺母	N-09104B001-G	黄铜	金 AUF	1
3	胶芯	T-09104T003-W	铁弗龙	白色	1
2	主体	B-D9104B003-G	黄铜	金 AUF	1
1	主体	B-D9104B001-G	黄铜	金 AUF	1
序号	名称	零件编号	材质	电镀/颜色	数量

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

315-1000 ±1.6

CHECKED BY GENIUS

30-120 ±0.6

UNIT/mm

SCALE 1:1

0.5-5 ±0.2

DATE

6-30 ±0.4

1000-2000 ±2.4

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

照片框

ORDER INFORMATION

SMB-PCR-174-LF
SERIES | LEADFREE
RG 174
90°
CRIMP
MALE

DESCRIPTION:

SMB

ELECTRICAL
IMPEDANCE
FREQUENCY

- 50 OHM
- 0-4 GHz
- 1.3MAX
- 1.5MAX

VSWR STRAIGHT
 RIGHT ANGLE

DIELECTRIC WITHSTANDING VOLTAGE
WORKING VOLTAGE

- 750 VOLTS RMS MAX, AT SEA LEVEL
- 250 VOLTS RMS MAX, AT SEA LEVEL

INSULATION RESISTANCE

- 1000 MEGOHMS MIN

CONTACT INNER CONDUCTOR
RESISTANCE OUTER CONDUCTOR

- 6 MILLIOHMS MAX.
- 2.5 MILLIOHMS MAX.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION 

0.5-5	0.2
5-30	=±0.4
30-120	=±0.6
120-315	=±1
315-1000	=±1.6
1000-2000	=±2.4

照片框

ORDER INFORMATION

SMB-PCR-174-LF
SERIES | | | LEADFREE
 | | | RG 174
 | 90°
 | CRIMP
 | MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: