

RECOMMENDED SOLDERING LAYOUT

**ELECTRICAL PERFORMANCE:**

1. IMPEDANCE : 50 Ohms
2. FREQUENCY : 0~6 GHz
3. WORKING VOLTAGE : 170 Vrms MAX
4. DIELECTRIC WITHSTANDING VOLTAGE : 500 Vrms max
5. INSULATOR RESISTANCE : 1000 MegOhms MIN

**SMCX-PW-50-LF**  
LEADFREE

**RoHS Compliant**

CONTACT	BRASS	GILD 30u"
INSULATOR	TEFLON	NONE
BLDY	BE. COPPER	GILD
DESCRIPTION	MATERIALS	FINISHED

**MORE THAN ALL**  
CONNECTORS  
ASSEMBLIES

PART NO. **SMCX-PW-50**

DWG NO. **SMCX-PW-50**

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

DESCRIPTION:

SMCX STRAIGHT PLUG  
EDGE MOUNT RECEPTACLE

AREA

REVISIONS

HK

DATE

焜倫股份有限公司