



P.C.B. LAYOUT  
(印刷电路板配置)

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
  3. GOLD PL 30 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
  4. TEFLON MIL-P-19468

	CONTACT PIN	NOTE 1	NOTE 3	
	INSULATOR	NOTE 4	WHITE	
	BODY	NOTE 1	NOTE 2	
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

SMP-PD-50-LF  
SERIES | LEADFREE  
50 OHM  
DIP 180°  
MALE

DESCRIPTION: SMP PCB MOUNT PLUG