



SPECIFICATION 仕様	
CONTACT RESISTANCE 接触抵抗	30 mΩ or less at 10mA (INITIAL)
INSULATING W/ INCREASING VOLTAGE 絶縁電圧	700 V.A.C for 1 minute
INSULATION RESISTANCE 絶縁抵抗	1000 MΩ or more at 500V.D.C
RATED CURRENT 定格電流	1A
OPERATING TEMPERATURE 作動温度	-65℃~150℃
RETENTION FORCE 保持力	0.5kg for 1 minute
INSERTION 挿入	10000 cycle (MECHANICAL)
ACTUATION FORCE 力付一歩動力	MAX. 1.4 kg

NOTES

- *印面寸法は、参考値となりますので、実物による適合確認が必要です。
IT IS REQUIRED TO CHECK THE ACTUAL MATCHING DETAIL BETWEEN THE PACKAGE AND SOCKET.
- THIS SOCKET CONCEPT IS REGISTERED PATENT.
(U.S.P. 4691975, JPN.P. 1869849)

符号 SYM.	品名 NAME	材質 MAT'L	数量 Q'TY	備考 REMARKS
5	COIL SPRING コイルスプリング	SUS	4	
4	CONTACT PIN FP用コタネピン*LB6*	BeCu	14	
3	CONTACT PIN FP用コタネピン*LA0*	BeCu	14	
2	カバー COVER	P.E.I	1	
1	本体 BODY	P.E.I	1	

SOP065-D-28-LF
LEADFREE
RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. SOP065-D-28

DWG NO. SOP065-D-28

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X±0.2
.XX±
.XXX±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司