



3&02817,1*

| Model No. | POS.1 | POS.2 |
|-------------|-------|-------|
| | | |
| SPSW08 | OFF | (ON) |
| Term. Comm. | OPEN | |
| SCHEMATIC | | |

SWITCH FUNCTION

SPECIFICATIONS

- MECHANICAL LIFE:** 50,000 make-and-break cycles.
- CONTACT RESISTANCE:** 20 mΩ max. initial @ 2-4VDC
100mA for both silver and gold plated contacts.
- INSULATION RESISTANCE:** 1,000 MΩ min.
- DIELECTRIC STRENGTH:** 1,000 Vrms min. @sea level.
- OPERATING TEMPERATURE:** -40°C to 85°C.

MATERIALS

- CASE & BUSHING** - Glass filled nylon 6/6, flame retardand, heat stabilized (UL94V-0).
- PLUNGER** - Thermoplastic Polyester (UL 94V-0), with intenal O-ring seal.
- CONTACT** - Brass.
- TERMINAL** - Copper.
- RoHS & Lead Free**

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

| | | |
|-------------------|-------------|---|
| DRAWING BY CY | | X, ± .X ± 0.40 .XX ± 0.25 .XXX ± ANG ± 5° |
| CHECKED BY GENIUS | | |
| UNIT / mm | SCALE 1 : 1 | |
| DATE | | |
| SIZE A4 | PJECTION | |

照片框

ORDER INFORMATION

SPSW08-D188-1X02-LF
 SERIES | LEADFREE
 02 WAY
 HIGH 18.85mm
 DIP 180°

DESCRIPTION: