



1. Specification

1.1 Electrical:

Contact Resistance: 20mΩ MAX
 Insulation Resistance: 1000MΩ
 Dielectric Withstand: No discharge, flashover or breakdown at 1000VAC 1Minute
 Life Cycle: 30,000 Cycles

1.2 Operation Temperature:

-30~+85°C

2. Material

Body: Nylon
 Terminals: Copper alloy
 Contact: Copper alloy
 Actuator: Nylon
 Housing: Nylon (UL94V-0)



schematic

Model No.	Switching Position	
SPSW12	OFF	(ON)
Term. Comm.	1-3	1-2

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ±

PJECTION

照片框

ORDER INFORMATION

SPSW12-D239-1X03E3-LF

SERIES

LEADFREE
 03 WAY EMPTY#3
 HIGH 23.9mm
 DIP 180°

DESCRIPTION:

SPST Sealed Snap-Acting Momentary Pushbutton Switches