



NOTE :

1. THICKNESS: 0.40 mm

SUS 301 : 0.25 mm

2. INSPECTION STANDARD ACCORDING TO MES PA 67001A SPECIFICATIONS

Item NO.	SECTION A-A	SECTION B-B	SURFACE TREATMENT	WIRE RANGE (mm <sup>2</sup> )	A	B	D
SPT-FT-20	W1=2.8 H1=2.8	W2=2.2 H2=2.2	PRE-TIN	0.2-0.5mm <sup>2</sup>	2.5	3.8	19.5
SPT-FT-16	W1=3.9 H1=4.1	W2=2.8 H2=3.0	PRE-TIN	0.5-1.0mm <sup>2</sup>	3	4.2	19.5
SPT-FT-14	W1=4.8 H1=4.9	W2=3.8 H2=4.1	PRE-TIN	1.0-2.5mm <sup>2</sup>	3.5	4.7	19.5
SPT-FT-12	W1=5.5 H1=5.7	W2=4.6 H2=4.8	PRE-TIN	2.5-4.0mm <sup>2</sup>	4	5.2	19.5

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

照片框

ORDER INFORMATION

SPT-FT-xx-LF  
SERIES | LEADFREE  
20:0.2-0.5mm<sup>2</sup>  
16:0.5-1.0mm<sup>2</sup>  
FEMALE | 14:1.0-2.5mm<sup>2</sup>  
12:2.5-4.0mm<sup>2</sup>  
TERMINAL

DESCRIPTION: