



Technical Data

Material:

Pin(outer sleeve): Brass,machined CuZn38Pb2

Plating(outer sleeve):

Tin plated:2µm/80µ"Ni, 5µm/200µ"Sn

Gold Plated:2µm/80µ"Ni,Full gold

Insulator(black): Black (PPS) UL94V-0

Electrical:

Current rating: 3Amps/contact max.

Contact resistance: ≤4mΩ/contact

Insulation resistance: ≥5000MΩ at V=500V

Dielectric Withstanding Voltage: 1000V AC Min

Operaing voltage: 60VAC/DC

Mechanical:

Operaing temperatures: Gold Plsted:-55°C to+125°C

Tin plated:-40°C to+105°C

Soldering temperature: +260°C,10s max.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

SPW-Dx-1Xxx-LF
SERIES | LEADFREE
1X02:02WAY
1X40:40WAY
T:TIN
G:GOLD
180°

DESCRIPTION: 2.54mmPitch SIP Adapters Welded Splice Pin Length 12.75mm

煜倫股份有限公司

www.morethanall.com