



Technical Data

Material:

Pin(outer sleeve): Brass,machined CuZn38Pb2

Clip(contact 6 finger): Beryllium Copper,heat treated

Plating(outer sleeve):

Tin plated:2µm/80µ"Ni, 5µm/200µ"Sn

Gold Plated:2µm/80µ"Ni,Full gold

Plating(contact): 2mm/80m"Ni, gold or Tin plated

Electrical

Current rating:3Amps/contact max.

Contact resistance: ≦ 4mΩ/contact

Mechanical:

Average insertion force with steel pin
of ø1.0mm, 6 - finger<300g

Average withdrawal force with steel pin
of ø1.0mm, 6 - finger>75g

Mechanical life cycle:min.200

SS-DKXT-1.0-LF
LEADFREE

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. SS-DKXT-1.0

DWG NO. SS-DKXT-1.0

FILE NO.

CHECKED BY CY

DRAWING BY

TOLERANCES ARE

X. ± 0.50

.X ± 0.30

.XX ± 0.20

.XXX ± 0.10

ANG

DESCRIPTION: ø2.35*ø1.90*L5.65mm 圆孔PIN

焯倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION



AREA

REVISIONS

DATE