

RECOMMEND P.C.BOARD LAYOUT  
(COMPONENT SIDE PCB:1.60mm)  
TOLERANCE:±0.05mm

NOTES :

1. MATERIAL :  
INSULATOR : GLASS FILLED POLYESTER, UL 94 V-0 RATED OR OTHER EQUIVALENT RESINS.  
TERMINAL : COPPER ALLOY
2. FINISH: GOLD PLATING IN THE CONTACT AREA AND SELECTIVE PLATING IN THE SOLDERTAIL AREA WITH 50u"(min.) NICKEL UNDERPLATING OVERALL.
3. ELECTRICAL CHARACTERISTIC :  
(1) Operating Temperature :  
105(max.) Degree C  
(2) Current Rating :  
Power Contact: 30A 600Vac  
Signal Contact: 1A 600Vac  
(3) Insulation Resistance :  
Power Contact: 1000 megohms(500 volt direct current)  
Signal Contact: 500 megohms(500 volt direct current)

SIGNAL		Ux/Tx/Sx/Rx
TYPE1		6.8mm

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm SCALE 1:1

DATE

SIZE A4


X, ±  
.X ± 0.25  
.XX ± 0.15  
.XXX ± 0.10  
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

SSI-PRZ-4+24+4-LF



DESCRIPTION: HIGH POWER CONNECTOR R/A RECEPTACLE