


RECOMMENDED  
CABLE STRIPPING DIM'S  
(建議剝線尺寸)



1. CONTACT PIN TO SOLDER  
(中心針銲接)

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
  3. GOLD PL 30 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
  4. TEFLON MIL-P-19468
  5. BERYLLIUM COPPER PER QQ-C-530

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY
	COVER	NOTE 1	NOTE 2	
	SHELL	NOTE 1	NOTE 2	
	GASKET	SILICONE	RED	
	C RING	NOTE 5	NONE	
	CONTACT PIN	NOTE 1	NOTE 3	
	INSULATOR	NOTE 4	WHITE	
	BODY	NOTE 1	NOTE 2	

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



照片框

**ORDER INFORMATION**

SSMA-PCR-085-LF

SERIES | | | LEADFREE  
| | | RG85  
| | | 90°  
| | | CRIMP  
| | | MALE

DESCRIPTION: