



### MATERIAL & FINISH

- \*precision swiss screw machine contact tap entry for easy insertion.
- \*4 fingers contact for very low insertion force.
- \*resistance to solder heat : Up to 260°C 1 minute without any plastic deformation.
- \*Insulator: Polyphenylene sulphide (PBT) UL 94V-0
- \*standard color:black
- \*contact:inner clip,beryllium copper. 5u"/ 10u' or 30u',gold over 50u" nickel.  
Outer sleeve, brass, 150u" tin over 50u" nickel or 10u" gold over nickel.
- \*contact resistance:Max. 10 Milliohm
- \*Insulation resistance: 5000 Mege Ohm at 500 VDC.
- \*Dielectric Withstanding voltage: 1000 VAC (RMS) minimum.
- \*Temperature rating: -55°C to +175°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

SSP-D-1Xxx-LF  
SERIES | LEADFREE  
1X01WAY  
1X40WAY  
DIP 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 2.54mm Pin Header SMD