



| ITEM | SPECIFICATION |
|------|---------------|
| T | 0.35 ±0.03 |
| D | ∅3.05 ±0.05 |
| D1 | ∅3.0 ±0.05 |
| W | 3.1 ±0.30 |
| H | 3.5 ±0.20 |
| L | 15.3 ±0.30 |
| E | 9.9 ±0.30 |
| F | 3.0 ±0.30 |

| WIRE GAUGE AWG | DIMENSIONS T x W x P | STD PKG Q'TY | NW KGS | MATERIAL /FINISH | SURFACE PROCESS | SERIAL OR SINGLE TYPE |
|-------------------|-------------------------|-----------------|-----------|---------------------|--------------------|--------------------------|
| 16-20 | -- | 7500 | -- | C2680 H C5191-H | Unplating BRASS | Serial |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT/mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG±

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

STA-23B-16-LF
SERIES | T LEADFREE
16-20 AWG
BRASS
2.35∅

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: