



P1	Red	P2	1
5	Blue	Blue	2
4	Black	Black	3
3	Red	Red	4
2	Blue	Blue	5
1			
	<u>PIN OUT</u>		

Electrical Properties

- 1.100% Test(Open Short Miss Wire)
- 2.Contact Resistance: 3Ω Maximum
- 3.Insulation Resistance: 1MΩ Minimum
- 4.Hi-Pot: 50V 10ms

4	H.S. TUBE	∅2.0mm L=60mm Color:Black	1PCS
3	WIRE	UL10064 32AWG OD=0.38mm(STD) Color:Ref. Pin Out	5PCS
2	TERMINAL	0.8mm Phosphor Bronze Gold Plated	10PCS
1	HOUSING	0.8mm 5Pin 刺破式 Nylon66 UL94-V0 White	2PCS
ITEM	PARTS NAME	SPECIFICATION STANDARD	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ± 0.35
.XX ± 0.25
.XXX ± 0.15
ANG ±

PPOJECTION



ORDER INFORMATION

SURX2-050532HT2-F10C-LF
SERIES | LEADFREE
| 100mm
| FEMALE TO FEMALE
| NON 1 TO 1
5 PIN TO 5 PIN | HEAT SHRINK TUBING
32 AWG

DESCRIPTION: Wire Harness 0.80mm 5Pin To 0.80mm 5Pin UL10064#32 L=100mm