


Electrical Properties

- 1.100% Test(Open Short Miss Wire)
- 2.Contact Resistance:3Ω Maximum
- 3.Insulation Resistance:1MΩ Minimum
- 4.Hi-Pot: 50V 10ms



3	WIRE	UL10064 32AWG OD=0.38mm(STD) Color:Ref. Pin Out	5PCS
2	TERMINAL	0.8mm Phosphor Bronze Gold Plated	10PCS
1	HOUSING	0.8mm 5Pin 刺破式 Nylon66 UL94-V0 White	2PCS
ITEM	PARTS NAME	SPECIFICATION STANDARD	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X ±
.X ± 0.35
.XX ± 0.25
.XXX ± 0.15
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

SURX2-050532W2-F10C-LF

SERIES

WIRE

32 AWG
05 TO 05 WAY

100mm

FEMALE

LEADFREE

DESCRIPTION: Wire Harness 0.80mm 5Pin To 0.80mm 5Pin UL10064#32 L=100mm