


Specification


Current Rating : 1A AC/DC
 Voltage Rating : 50V AC/DC
 Withstand Voltage : 500V AC/Minute
 Insulation Resistance : 500MΩ MIN.
 Temperature Range : -25° C To +85° C
 Applicable Wire : AWG #26 To #30
 Applicable P.C.B Thickness : 0.8 - 1.6mm
 Applicable P.C.B Hold Dia. : Ø 0.7 ± 0.05

Contact Information


Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
SZN-T-26	AWG#26-#30	1.00mm MAX.	Brass	See note	15,000 pcs



SEC:A-A



SEC:B-B



SEC:C-C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±
 .X±
 .XX±
 .XXX±
 ANG±

PJECTION

照片框

ORDER INFORMATION

SZN-T-26-LF
 SERIES | T LEADFREE
 26~30 AWG
 TERMINAL

DESCRIPTION: 1.50mm PITCH BOARD-IN CRIMP TERMINAL 180°