


Specification


Current Rating : 1A AC/DC
 Voltage Rating : 50V AC/DC
 Withstand Voltage : 500V AC/Minute
 Insulation Resistance : 500MΩ MIN.
 Temperature Range : -25° C To +85° C
 Applicable Wire : AWG #26 To #30
 Applicable P.C.B Thickness : 0.8 - 1.6mm
 Applicable P.C.B Hold Dia. : $\varnothing 0.7 \pm 0.05$

Contact Information


Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
SZR-T-26	AWG#26-#30	1.00mm MAX.	Brass	See note	15,000 pcs



SEC:A-A



SEC:B-B



SEC:C-C

SZR-T-26-LF
LEADFREE

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. SZR-T-26

DWG NO. SZR-T-26

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2

.XX ±

.XXX ±

AWG

DESCRIPTION:

1.50mm PITCH BOARD-IN
CRIMP TERMINAL 90°

AREA

REVISIONS

HK

DATE

焯倫股份有限公司