


Recommended P.C.Board Layout
(Tolerance: ±0.05)




Specifications
 Current Rating: 3Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding Voltage: 600VAC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C
 Materials
 Contact Material: Brass
 Insulator Material: High Temperature Thermoplastic, UL 94V-0 Nylon 6T (Halogen Free) or the equivalent material


NO.	A	B	Insulator Material	Standard Packing
02	2.54	5.08	Nylon 6T(Halogen Free)	Box
03	5.08	7.62	Nylon 6T(Halogen Free)	Box
04	7.62	10.16	Nylon 6T(Halogen Free)	Box
05	10.16	12.70	Nylon 6T(Halogen Free)	Box
06	12.70	15.24	Nylon 6T(Halogen Free)	Box
07	15.24	17.78	Nylon 6T(Halogen Free)	Box
08	17.78	20.32	Nylon 6T(Halogen Free)	Box
09	20.32	22.86	Nylon 6T(Halogen Free)	Box
10	22.86	25.40	Nylon 6T(Halogen Free)	Box
11	25.40	27.94	Nylon 6T(Halogen Free)	Box
12	27.94	30.48	Nylon 6T(Halogen Free)	Box
13	30.48	33.02	Nylon 6T(Halogen Free)	Box
14	33.02	35.56	Nylon 6T(Halogen Free)	Box
15	35.56	38.10	Nylon 6T(Halogen Free)	Box
16	38.10	40.64	Nylon 6T(Halogen Free)	Box
17	40.64	43.18	Nylon 6T(Halogen Free)	Box
18	43.18	45.72	Nylon 6T(Halogen Free)	Box
19	45.72	48.26	Nylon 6T(Halogen Free)	Box
20	48.26	50.80	Nylon 6T(Halogen Free)	Box
21	50.80	53.34	Nylon 6T(Halogen Free)	Box
22	53.34	55.88	Nylon 6T(Halogen Free)	Box
23	55.88	58.42	Nylon 6T(Halogen Free)	Box
24	58.42	60.96	Nylon 6T(Halogen Free)	Box
25	60.96	63.50	Nylon 6T(Halogen Free)	Box
26	63.50	66.04	Nylon 6T(Halogen Free)	Box
27	66.04	68.58	Nylon 6T(Halogen Free)	Box
28	68.58	71.12	Nylon 6T(Halogen Free)	Box
29	71.12	73.66	Nylon 6T(Halogen Free)	Box
30	73.66	76.20	Nylon 6T(Halogen Free)	Box
31	76.20	78.74	Nylon 6T(Halogen Free)	Box
32	78.74	81.28	Nylon 6T(Halogen Free)	Box
33	81.28	83.82	Nylon 6T(Halogen Free)	Box
34	83.82	86.36	Nylon 6T(Halogen Free)	Box
35	86.36	88.90	Nylon 6T(Halogen Free)	Box
36	88.90	91.44	Nylon 6T(Halogen Free)	Box
37	91.44	93.98	Nylon 6T(Halogen Free)	Box
38	93.98	96.52	Nylon 6T(Halogen Free)	Box
39	96.52	99.06	Nylon 6T(Halogen Free)	Box
40	99.06	101.60	Nylon 6T(Halogen Free)	Box

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY X. ± 0.30
 CHECKED BY GENIUS .X ± 0.25
 UNIT / mm SCALE 1 : 1 .XX ± 0.15
 DATE .XXX ± 0.10
 SIZE A4 PPROJECTION ANG ±



ORDER INFORMATION



DESCRIPTION: 2.54 PIN HEADER DUAL ROWS DIP TYPE CONNECTOR

www.morethanall.com