

DIMENSION :  $\pm 0.8$  PITCH 11.0mm

P數	2	3	4	5	6	7	8	9	10	11	12	13	14
A	33	44	55	66	77	88	99	110	121	132	143	154	165
B	41	52	63	74	85	96	107	118	129	140	151	162	173

P數	15	16	17	18	19	20	21	22	23	24	25	26
A	176	187	198	209	220	231	242	253	264	275	286	297
B	184	195	206	217	228	239	250	261	272	283	294	305

### SPECIFICATIONS

#### SPECIFICATIONS

Rated: 20A 300VAC  
 Insulation Withstands Voltage: AC 2000V/min  
 Insulation Resistance: 1000M $\Omega$  or More at DC500V  
 Using Temperature Range:  $-40^{\circ}\text{C} \sim +120^{\circ}\text{C}$   
 Screw Torque Value: 12 Kg-cm  
 Wire Range Awg: 12 - 18 STR  
 Insulator Body : Plastic NYLON 66 (UL 94V-0)  
 Terminals: Brass, Tin Plated 0.8t  
 Terminal Screws: M3.5 Nickel Plated Brass

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

PJECTION

X,  $\pm$   
 X,  $\pm$   
 .XX  $\pm$   
 .XXX  $\pm$   
 ANG  $\pm$



### ORDER INFORMATION

TBA110-W-xx-LF  
 SERIES | LEADFREE  
 02-26WAY  
 WIRE TO WIRE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: