

**SPECIFICATIONS**

BARRIER MATERIAL: THERMOPLASTIC (UL 94V-0).BLACK  
 TERMINALS: TIN PLATED BRASS  
 SCREW: NICKEL PLATED STEEL  
 WIRE RANGE:18-22 STR  
 RATING: 10 AMPERES,300VAC  
 INSULATION WITHSTANDS VOLTAGE AC 2000V  
 INSULATION RESISTANCE 500M OR MORE AT DC 500V

**DIMENSION:±0.5**

POLE	2	3	4	5	6	7	8	9	10
A	16.76	24.38	32	39.62	47.24	54.86	62.48	70.1	77.72
B	7.62	15.24	22.86	30.48	38.1	45.72	53.34	60.96	68.58
POLE	11	12	13	14	15	17	18	19	20
A	85.34	92.96	100.6	108.2	115.8	131.06	138.68	146.3	153.92
B	76.2	83.82	91.44	99.06	106.7	121.92	129.54	137.16	144.78
POLE	21	22	23	24	25	26	27	28	29
A	161.54	169.16	176.78	184.4	192.02	199.64	207.3	214.9	222.5
B	152.4	160.02	167.64	175.26	182.88	190.5	198.1	205.7	213.4
POLE	30	31	32						
A	230.1	237.7	245.4						
B	221	228.6	236.2						

**RoHS Compliant**

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES


煜倫股份有限公司

www.morethanall.com

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT/mm SCALE 1:1  
 DATE  
 SIZE A4 PROJECTION

TOLERANCES ARE

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±



**ORDER INFORMATION**

TBB076-D15-xx-LF  
 SERIES | LEADFREE  
 02~32WAY  
 PIN LONG 15.0mm  
 DIP 180°

DESCRIPTION: PITCH 7.62 mm