



N= Number of contacts

MATERIALS ELECTRICAL  
 RATED VOLTAGE & CURRENT: 250 V, 15 A  
 WITHSTAND VOLTAGE: AC 2000 V/Min  
 INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V  
 OPERATING TEMPERATURE RANG: -40 °C ~ +115 °C  
 SCREW TORQUE VALUE: 5.3 Lb-In.  
 WIRE RANGE: 22 - 16 AWG  
 1) MOLDED PARTS: Thermoplastic, UL 94 V-0 BLACK  
 2) TERMINAL: BRASS, 0.8t, Tin PLATED  
 3) TERMINAL SCREWS: STEEL, Ni PLATED, M3  
 APPROVAL:

DIMENSION		Poles	Tolerance
Dim A	$(N+2) \times 7.62 + 1.5$	2p-8p	±0.20
Dim B	$(N-1) \times 7.62$	9p-15p	±0.30
		16p-20p	±0.40
		21p-25p	±0.50
		26p-30p	±0.60

N=Number of contacts

TBB076-SE-xx-LF  
 LEADFREE  
 02~30WAY  
 RoHS Compliant

**MORETHANALL**  
 CONNECTORS  
 ASSEMBLIES

煜倫股份有限公司

PART NO. TBB076-SE-xx		CHECKED BY CY	TOLERANCES ARE .X ± 0.3 .XX ± 0.3 .XXX ± ANG	DESCRIP TION:			
DWG NO. TBB076-SE-xx							
FILE NO.		PROJECTION	AREA	REVISIONS	HK	DATE	
UNIT / mm	SCALE 1:1						