

SPECIFICATIONS

BARRIER MATERIAL : THERMOPLASTIC (UL 94V-0),BLACK
 TERMINALS : TIN PLATED BRASS
 SCREWS : NICKEL PLATED STEEL
 WIRE RANGE AWG : 16-22 STR.
 RATING : 15 AMPERES,300 VAC
 INSULATION WITHSTANDS VOLTAGE AC 2000V/MIN
 INSULATION RESISTANCE 500M OHM OR MORE AT DC 500V

DIMENSION: ±0.5

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15				
A	18.5	26.75	14.25	43.25	51.5	59.75	68	76.25	84.5	92.75	101	109.3	117.5	125.8				
B	8.25	16.5	24.75	43.25	41.25	49.5	57.75	66	74.25	82.5	90.75	99	107.3	115.5				
POLE	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	
A	134	142.25	150.5	158.75	167	175.25	183.5	191.75	200	208.25	216.5	224.8	233	241.3	249.5	257.8	266	
B	123.75	132	140.25	148.5	156.75	165	173.25	181.5	189.75	198	206.25	214.5	222.8	231	239.3	247.5	255.8	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT/mm SCALE 1:1

DATE

SIZE A4

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION



ORDER INFORMATION

TBB082-R-xx-LF

SERIES | LEADFREE
 02~32WAY
 DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: