


# SPECIFICATIONS

- ① Housing Material: Polyamide 66(UL94V-0), Black
- ② Screw: M3.5 Nickel Plated Steel
- ③ Terminals: Tin Plated Brass
- ④ Cover: PC Transparent

Screws Torque: 12 In-Lb  
 Wire Range: 14~22 AWG  
 Rated: 10 Amperes.AC250V  
 Operation Temperature: -55°C~+95°C  
 Insulation withstands volt: AC2000V min  
 Insulation resistance: >1000MΩ or more at DC500V



Tolerance ± 0.50

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15				
A	21.1	30.6	40.1	49.6	59.1	68.6	78.1	87.6	97.1	106.6	116.1	125.6	135.1	144.6				
B	9.5	21.1	28.5	38	47.5	57	66.5	76	85.5	95	104.5	114	123.5	133				
POLE	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	
A	154.1	163.6	173.1	182.6	192.1	201.6	211.1	220.6	230.1	239.6	249.1	258.6	268.1	277.6	287.1	296.6	306.1	
B	142.5	152	161.5	171	180.5	190	199.5	209	218.5	228	237.5	247	256.5	266	275.5	285	294.5	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

P PROJECTION



ORDER INFORMATION

TBB095-D-xx-LF  
 SERIES | LEADFREE  
 02~32 WAY  
 DIP 180°

DESCRIPTION: Barrier type terminal block