

SPECIFICATIONS

BARRIER MATERIAL: THERMOPLASTIC (UL 94V-0).BLACK

TERMINALS: TIN PLATED BRASS

SCREWS:NICKEL PLATED STEEL

WIRE RANGE AWG: 14-22 STR

RATING: 10AMPERES.250VAC

INSULATION WITHSTANDS VOLTAGE AC 2000V

INSULATION RESISTANCE 500M OR MORE AT DC 500V

| POLE | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | | | |
|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-----|-----|
| A | 40.1 | 49.6 | 59.1 | 68.6 | 78.1 | 87.6 | 97.1 | 106.6 | 116.1 | 125.6 | 135.1 | 144.6 | 154.1 | 163.6 | | | |
| B | 28.5 | 38 | 47.5 | 57 | 66.5 | 76 | 85.5 | 95 | 104.5 | 114 | 123.5 | 133 | 142.5 | 152 | | | |
| POLE | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 | 32 |
| A | 173.1 | 182.6 | 192.1 | 201.1 | 211.1 | 220.6 | 230.1 | 239.6 | 249.1 | 258.6 | 268.1 | 277.6 | 287.1 | 296.6 | 306.1 | --- | --- |
| B | 161.5 | 171 | 180.5 | 190 | 199.5 | 209 | 218.5 | 228 | 237.5 | 247 | 256.5 | 266 | 275.5 | 285 | 294.5 | --- | --- |

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4


X, ±
X, ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

TBB095-R4E-xx-LF



DESCRIPTION:

煜倫股份有限公司

www.morethanall.com