



- MATERIALS ELECTRICAL cULus CQC
- ⚠️ RATED VOLTAGE & CURRENT: 300 V, 30 A / 300V 25A
- WITHSTAND VOLTAGE: AC 2000 V/Min / AC2500V/min
- INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V
- OPERATING TEMPERATURE RANG: -40 °C ~ +115 °C
- SCREW TORQUE VALUE: 10.54 Lb-In. / 1.2 Nm
- ⚠️ WIRE RANGE: 22 - 10 AWG / 22-14 AWG ⚠️
- 1) MOLDED PARTS: Thermoplastic, UL 94 V-0 BLACK
- 2) TERMINAL: BRASS, 0.8t, Tin PLATED
- 3) TERMINAL SCREWS: STEEL, Ni PLATED, M3.5
- ⚠️ Critical dimension: ▽
- ⚠️ APPROVAL:

⚠️ N = Number of poles
 Dim A = $N \times 9.5 + 1.5$ ⚠️
 Dim B = $(N - 1) \times 9.5$

Poles	Tol.	Dim A&B
2-4p		±0.20
5-8p		±0.25
9-16p		±0.35
17-23p		±0.40
24-30p		±0.50

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION

TBC095-RD12-xx-LF

SERIES

LEADFREE

02~30WAY

DIP 12.0mm

DIP 90°

DESCRIPTION: