



MATERIALS ELECTRICAL

- △ RATED VOLTAGE & CURRENT: 300 V, 20 A
- WITHSTAND VOLTAGE: AC 2000 V/Min
- INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V
- △ OPERATING TEMPERATURE RANG: -40 °C ~ +115°C
- △ SCREW TORQUE VALUE: 11Lb-In
- WIRE RANGE: 22-12 AWG
- 1) MOLDED PARTS: Thermoplastic ( UL 94 V-0 )
- 2) TERMINAL: BRASS, 1.2t, Tin PLATED
- 3) TERMINAL SCREWS: STEEL, Ni PLATED, M4
- △ APPROVAL:

Dimension A&B&C

DIM A	$N \times 11.0 + 0.2$	△
DIM B	$(N-1) \times 11.0$	
DIM C	$(N+1) \times 11+1$	

N=Number of contacts

Poles	A&B Tolerance
2P-8P	±0.20
9P-14P	±0.30
15P-20P	±0.40
21P-24P	±0.50
25P-30P	±0.60

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

TBC110-RPE-xx-LF

SERIES | LEADFREE  
02~30WAY  
PANEL EAR  
DIP 90°

DESCRIPTION: