


### Material

- Terminal body (metal housing): Brass(CuZn)
- Terminal screw: Steel Zinc plating "-" slot type
- Wire guard: Steeless steel
- Insulator (housing): Thermoplastic (UL94V-0)

### △ Electrical UL/cUL

- Voltage rating: 400VAC/400VAC
- Current rating: 8A/8A
- Wire range:
- Solid wire(AWG): none/14-22
- Stranded wire(AWG): 14-22/14-22
- Torque(Lb-In): 3.5
- Screw: M3
- Wire strip length: 7-8mm
- Withstanding Voltage: 1.8KV
- Operating temperature: -30°C to +105°C
- Safety Approval: 

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION 

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



### ORDER INFORMATION

TBFB100-W-03-LF

SERIES | LEADFREE  
03 WAY  
WIRE TO WIRE

DESCRIPTION: