



2p to 6p with wedge, above 7p
without wedge (including 7p)

N = Number of contacts

Material

- Item ①; Terminal body (metal housing): Brass (CuZn), Nickel plated
- Item ②; Terminal screw: Steel Zinc plating "-" slot type
- Item ③; Wire guard: PhBz, Tin plated
- Item ④; Insulator (housing): Thermoplastic (UL94V-0)
- Item ⑤; Insulator (cover): Thermoplastic (UL94V-0)

Electrical cULus/VDE

- Voltage rating: 300V \bar{A} C/300VAC
- Current rating: 8A/8A
- Wire range: 1.5mm
- Solid wire (AWG): 16-28
- Stranded wire (AWG): 16-28
- Torque: 1.7Lb-In./0.2Nm
- Screw: M2
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV/2.5KV
- ▲ ● Operating temperature: -40°C to +115°C
- ▲ ● Safety approval:

DIMENSION

A	NX3.5
B	(N-1)X3.5

Poles	Tolerance
2P-8P	±0.10
9P-16P	±0.20
17P-24P	±0.30

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ± 0.50

.X, ± 0.30

.XX, ± 0.10

.XXX, ±

ANG ± 1°

P PROJECTION

照片框

ORDER INFORMATION

TBH035-SVCB-xx-LF

SERIES

LEADFREE
02~24WAY
BOTTOM KEY
CAGE
SCREW 180°
FEMALE

DESCRIPTION: