



**Material**

- Item Ⓞ Clamp: Steel zinc plated.
- Item Ⓞ Terminal screw: Brass Zinc plating "-" slot type
- Item Ⓞ Female contact: PhBz Bright Tin plated over Nickel plated ⚠
- Item Ⓞ Terminal (Up body): Thermoplastic (UL94V-0)
- Item Ⓞ Terminal (Down body): Thermoplastic (UL94V-0)
- Item Ⓞ Clampage: Steel Zinc plated

- ⚠ Electrical cULus VDE
- Voltage rating: 300V 300V(II/2)
  - Current rating: 10A 10A
  - Wire range: 0.2-1.5mm<sup>2</sup>
  - Solid wire(AWG): 16-28
  - Stranded wire(AWG): 16-28
  - Torque: 1.7Lb-In / 0.2N.m
  - Screw: M2
  - Wire strip length: 6-7mm
  - Withstanding Voltage: 1.6KV
  - Rated impulse voltage(II/2): 2.5KV
  - Operating temperature: -40°C to +115°C
  - Safety approval: cULus ⚠
  - Critical dimension: ■

N = Number of poles ⚠

Dim A =  $N \times 3.81 + 0.8$

Dim B =  $(N-1) \times 3.81$

	Dim A	Dim B
2p	±0.20	±0.10
3P-6p	±0.20	±0.20
7P-12p	±0.25	±0.25
13P-18p	±0.30	±0.30
19P-24p	±0.40	±0.40

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ± 1°

SIZE A4

P PROJECTION

照片框

**ORDER INFORMATION**

TBHO38-SHC-xx-LF

SERIES | | | LEADFREE  
| | | 02-24WAY  
CAGE  
SCREW WIRE  
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: