

△ Material

- Item (a) Clamp: Brass(CuZn) Ni plated
- Item (b) Terminal screw: Steel Zinc plating “-” slot type
- △ ● Item (c) Female contact: PhBz ,Bright Tin plated over Nickel plated
- Item (d) Terminal (housing): Thermoplastic (UL94V-0)
- Item (e) Terminal (cover): Thermoplastic (UL94V-0)
- △ ● Item (f) With flange screw: steel M2.5 Zinc plating “+/-” slot type

△ △ Electrical cULus/VDE

- Voltage rating: 300VAC/300VAC
- Current rating: 10A/10.5A
- Wire range: 1.5mm²
- △ ● Solid wire(AWG): 16-28
- Stranded wire(AWG): 16-28
- Torque: 3Lb-In/0.2Nm
- Screw: M2
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV/2.5KV
- Operating temperature: -40°C to +115°C
- △ ● Safety Approval:
- △ ● Critical dimension: ▲

△ △ Dim.L = N x 3.81
 Dim.B = (N-1) x 3.81
 Dim.C = N x 3.81+10.08
 Dim.D = (N-1) x 3.81+9.0
 N= number of poles

△ Dim. \ poles Tolerance	2P-6P	7P-12P	13P-18P	19P-24P
Dim.L	±0.15	±0.20	±0.25	±0.30
Dim.B	±0.10	±0.15	±0.20	±0.25
Dim.C	±0.15	±0.20	±0.25	±0.30
Dim.D	±0.15	±0.20	±0.25	±0.30

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1


.XXX ±

DATE

ANG ± 1°

SIZE A4

P PROJECTION



ORDER INFORMATION

TBHO38-SWCF-xx-LF

SERIES | | | | LEADFREE
 | | | | 02-24WAY
 | | | | FLANGE
 | | | | CAGE
 | | | | SCREW 90°
 | | | | FEMALE

DESCRIPTION:

www.morethanall.com