



SPECIFICATIONS
BARRIER MATERIAL: THERMOPLASTIC (UL 94V-0) GREEN
TERMINALS: TIN PLATED BRASS
SCREWS: ZINC PLATED STEEL
WIRE RANGE AWG: 16-22 STR
RATING: 10 AMPERES, 250 VAC
INSULATION WITHSTANDS VOLTAGE AC 2000V
INSULATION RESISTANCE 500 Ω OR MORE AT DC 500V

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15
A	10.5	15.5	20.5	25.5	30.5	35.5	40.5	45.5	50.5	55.5	60.5	65.5	70.5	75.5
B	5	10	15	20	25	30	35	40	45	50	55	60	65	70
	16	17	18	19	20	21	22	23	24	25	26	27		
A	80.5	85.5	90.5	95.5	100.5	105.5	110.5	115.5	120.5	125.5	130.5	135.5		
B	75	80	85	90	95	100	105	110	115	120	125	130		

MORE THAN ALL
 CONNECTORS
 ASSEMBLIES

煜倫股份有限公司

PART NO. **TBH050-DR-xx**

DWG NO. **TBH050-DR-xx**

FILE NO.

UNIT / mm SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
 .XX ±
 .XXX ±
 AWG

DESCRIP TION:				
	AREA	REVISIONS	HK	DATE