



NOTES :  
 1. RoHS compliance  
 2. PCB 1.6±0.14

Total Pitch Tolerances		Normal dimension Tolerances	
0-30	±0.20	0-30	±0.25
over 30-53	±0.25	over 30-53	±0.30
over 53-70	±0.30	over 53-70	±0.35
over 70-90	±0.35	over 70-90	±0.44
over 90-115	±0.44	over 90-115	±0.55
over 115-150	±0.55	over 115-150	±0.70
over 150-200	±0.70	over 150-200	±0.85
over 200-250	±0.85	over 200-250	±1.00
over 250-320	±1.00	over 250-320	±1.20

P	2	3	4	5	6	7	8
A	5.00	10.00	15.00	20.00	25.00	30.00	35.00
B	10.00	15.00	20.00	25.00	30.00	35.00	40.00
P	9	10	11	12	13	14	
A	40.00	45.00	50.00	55.00	60.00	65.00	
B	45.00	50.00	55.00	60.00	65.00	70.00	

5	SCREW	STEEL	M2.5 Zn Plated
4	WIRE CAGE	STEEL	M2.5 Zn Plated
3	CLAMP	COPPER ALLOY	Tin Plated
2	COVER	PA66	UL94-V0 GREEN
1	HOUSING	PA66	UL94-V0 GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG±

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

TBH050-EW-xx-LF

SERIES | | T LEADFREE  
 | | | 02~14WAY  
 WIRE  
 EAR

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: