



| Total Pitch Tolerances | | Normal dimension Tolerances | |
|------------------------|-------|-----------------------------|-------|
| 0~30 | ±0.20 | 0~30 | ±0.25 |
| over 30~53 | ±0.25 | over 30~53 | ±0.30 |
| over 53~70 | ±0.30 | over 53~70 | ±0.35 |
| over 70~90 | ±0.35 | over 70~90 | ±0.44 |
| over 90~115 | ±0.44 | over 90~115 | ±0.55 |
| over 115~150 | ±0.55 | over 115~150 | ±0.70 |
| over 150~200 | ±0.70 | over 150~200 | ±0.85 |
| over 200~250 | ±0.85 | over 200~250 | ±1.00 |
| over 250~320 | ±1.00 | over 250~320 | ±1.20 |

| | | | | | | | | | | | | |
|---|-------|-------|-------|-------|-------|-------|--------|--------|--------|--------|--------|-------|
| P | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 |
| A | 5.00 | 10.00 | 15.00 | 20.00 | 25.00 | 30.00 | 35.00 | 40.00 | 45.00 | 50.00 | 55.00 | 60.00 |
| B | 10.00 | 15.00 | 20.00 | 25.00 | 30.00 | 35.00 | 40.00 | 45.00 | 50.00 | 55.00 | 60.00 | 65.00 |
| P | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | |
| A | 65.00 | 70.00 | 75.00 | 80.00 | 85.00 | 90.00 | 95.00 | 100.00 | 105.00 | 110.00 | 115.00 | |
| B | 70.00 | 75.00 | 80.00 | 85.00 | 90.00 | 95.00 | 100.00 | 105.00 | 110.00 | 115.00 | 120.00 | |

| | | | |
|------|--------------|--------------|------------|
| 2 | SOLDER PIN | COPPER ALLOY | Tin Plated |
| 1 | HOUSING | PA66 | |
| ITEM | NAME OF PART | MATERIAL | NOTES |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X.±
.X±
.XX±
.XXX±
ANG±

PJECTION

照片框

ORDER INFORMATION

TBH050-PD-xx-LF

SERIES T T LEADFREE
02~24WAY
DIP 180°
MALE

DESCRIPTION: