



	Material	Plating/Finish	Remark
1	Insulating body Polyamide 66(UL94V-0)		Green
2	Cage clamp Steel	Ni plated	
3	Terminal Brass	Tin plated	
4	Screw Steel	Ni plated	

Current rating : 16Amp 300V
 Insulation withstands volt : AC2000V min
 Insulation resistance : >2000MΩ DC500V
 Operation temperature : -40°C to +105°C
 Wire strip length : 4mm~5mm
 Wire range : 12~26 AWG
 Screw torque : 7.0 lb-inch

Pitch : 5.08mm(0.200inch)					
Poles	A(mm)	A(inch)	Poles	A(mm)	A(inch)
2	10.16	0.400	15	76.20	3.000
3	15.24	0.600	16	81.28	3.200
4	20.32	0.800	17	86.36	3.400
5	25.40	1.000	18	91.44	3.600
6	30.48	1.200	19	96.52	3.800
7	35.56	1.400	20	101.60	4.000
8	40.64	1.600			
9	45.72	1.800			
10	50.80	2.000			
11	55.88	2.200			
12	60.96	2.400			
13	66.04	2.600			
14	71.12	2.800			

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
 X, ±
 .XX ±
 .XXX ±
 ANG ±

照片框

ORDER INFORMATION

TBH051-D14S1-xx-LF

SERIES

LEADFREE
 02-20 WAY
 SOLID/ONE
 HIGH 14.0mm
 DIP 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: