



Material

- Item (a) Clamp: Brass(CuZn) Ni plated
- Item (b) Terminal screw: Steel Zinc plating "-" slot type
- Item (c) Female contact: PhBz ,Tin plated
- Item (d) Terminal (up body): Thermoplastic (UL94V-0)
- Item (e) Terminal (down body): Thermoplastic (UL94V-0)

Electrical cULus

- Voltage rating: 300VAC
- △ ● Current rating: 20A
- Wire range:
- △ ● Solid wire(AWG): 12-22
- △ ● Stranded wire(AWG): 12-22
- △ ● Torque: 4 Lb-In
- Screw: M3
- Wire strip length: 7-8mm
- Withstanding Voltage: 1.6KV
- △ ● Operating temperature: -40°C to +115°C
- Safety Approval:
- Critical dimension:

Dim.A=N×5.08

Dim.B=(N-1)×5.08

N=NUMBER OF CONTACTS

POLES	TOL Dim.A/B
2p-6p	±0.10
7p-12p	±0.20
13p-18p	±0.30
19p-24p	±0.40

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50

.X ± 0.30

.XX ± 0.10

.XXX ±

ANG ± 1°

PJECTION

照片框

ORDER INFORMATION

TBH051-SA-xx-LF

SERIES | LEADFREE
| 02-24WAY
| SLANT
| FEMALE

DESCRIPTION: