



SECTION A-A

TBH063-H26-xx-LF
LEADFREE
01-16WAY

Material

- Item a Terminal body; Thermoplastic (UL94V-0)
- Item b Terminal cover; Thermoplastic (UL94V-0)
- Item c Terminal screw ; Steel Zinc plating "-" slot type
- Item d Clampage; Steel/steel Zinc plated
- Item e Terminal body; Steel, Zinc plating
- Item f Solder pin; Copper, Tin plated

Electrical

- Voltage rating: 300VAC
- Current rating: 30A
- Wire range:
- Solid wire(AWG): 10-24
- Stranded wire(AWG): 10-24
- Torque(Lb-In): 4.3
- Screw: M3
- Wire strip length: 15-16mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec

- △ Critical dimension: ▽
- △ Safety Approval:

Poles	01	02	03	04	05	06	07	08
Dim L	7.85	14.2	20.55	26.9	33.25	39.6	45.95	52.3
Dim B		6.35	12.70	19.05	25.40	31.75	38.10	44.45
TOL	±0.10		±0.15		±0.20		±0.25	
Poles	09	10	11	12	13	14	15	16
Dim L	58.65	65.0	71.35	77.7	84.05	90.4	96.75	103.1
Dim B	50.80	57.15	63.50	69.85	76.20	82.55	88.90	95.25
TOL	±0.30		±0.35		±0.40			

RoHS Compliant

MORE THAN ALL
CONNECTORS
ASSEMBLIES

PART NO. TBH063-H26-xx

DWG NO. TBH063-H26-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ±
.XX ±
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

焯倫股份有限公司