



N = Number of poles
 Dim L = N x 7.62 + 1.5
 Dim P = (N - 1) x 7.62

	Dim L	Dim P
2-4p	±0.25	±0.20
5-7p	±0.30	±0.25
8-11p	±0.35	±0.30
12-16p	±0.40	±0.35

Material

- Item a Terminal body: Thermoplastic (UL94V-0)
- Item b Terminal cover: Thermoplastic (UL94V-0)
- Item c Terminal screw: Steel Zinc plating "-" slot type
- Item d Clampage: Steel, Zinc plated
- Item e Clamp: Steel, Zinc plating
- Item f Solder pin: Copper, Tin plated

Electrical

- Voltage rating: 300VAC
- Current rating: 30A
- Wire range:
- Solid wire(AWG): 10-24
- Stranded wire(AWG): 10-24
- Torque(Lb-In): 4.3
- Screw: M3
- Wire strip length: 15-16mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval:
- Critical dimension:

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
煜倫股份有限公司
 www.morethanall.com

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4 PPROJECTION

X. ± 0.50
 .X ± 0.30
 .XX ± 0.10
 .XXX ±
 ANG ± 1°



ORDER INFORMATION

TBH076-D26B-xx-LF
 SERIES | | | LEADFREE
 | | | 02-16 WAY
 | | | BOX
 | | | HIGH 26.0mm
 | | | DIP 180°

DESCRIPTION: