



Material:

- Item ① metal housing: Steel
- Item ② Insulator(housing): Thermoplastic (UL94V-0)
- Item ③ Wire guard: PhBz(CuSn),Tin plated.
- Item ④ Terminal screw: Steel Zinc plating "-" slot type

Electrical:

- | | |
|--------------------------|-----------------|
| | cULus |
| ● Voltage rating: | 300V |
| ● Current rating: | 20A |
| ● Wire range: | |
| ● Solid wire(AWG): | 12-30 |
| ● Stranded wire(AWG): | 12-30 |
| ● Torque: | 3.5 Lb-In. |
| ● Screw: | M2.5 |
| ● Wire strip length: | 8-9mm |
| ● Withstanding Voltage: | 1.6KV |
| ● Operating temperature: | -30°C to +105°C |

POLE		2	3	4	5	6	7	8	9	10	11	12	
A		13.24	20.86	28.48	36.10	43.72	51.34	58.96	66.58	74.20	81.82	89.44	
B		7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58	76.20	83.82	
Tol.		±0.10					±0.15						
POLE	13	14	15	16	17	18	19	20	21	22	23	24	
A	97.06	104.68	112.30	119.92	127.54	135.16	142.78	150.40	158.02	165.64	173.26	180.88	
B	91.44	99.06	106.68	114.30	121.92	129.54	137.16	144.78	152.40	160.02	167.64	175.26	
Tol.		±0.20						±0.30					

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

TBHO76-SH-xx-LF
SERIES | LEADFREE
02-24WAY
H TYPE
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: