



Material

- Item Clamp : Brass(CuZn) Ni plated
- Item Terminal screw:Steel Zinc plating"-slot type
- △ Item Female contact : Copper Tin plated
- Item Terminal (body):Thermoplastic (UL94V-0)
- Item Terminal (cover):Thermoplastic (UL94V-0)
- Item With flange screw:Steel Zinc plating M3 " slot type

Electrical a cULus

- Voltage rating: 300V
- Current rating: 20A
- Wire range:
 - Solid wire (AWG):10-30
 - Stranded wire(AWG):10-30
- Torque: 4.5(Lb-In)
- Screw:M3
- Wire strip length:7-8mm
- Withstanding Voltage:1.6KV
- Operating temperature:-40°C to +115°C
- △ Safety Approval: us

N = Number of poles
 Dim A=Nx7.62
 Dim B=(N-1)x7.62

	Dim A	Dim B
2-6p	±0.20	±0.20
7-12p	±0.30	±0.30
13-16p	±0.40	±0.40

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ±

PJECTION

照片框

ORDER INFORMATION

TBH076-SWCF30-xx-LF

SERIES

LEADFREE

02-16WAY

LONG 30.6mm

FLANGE

CAGE

SCREW WIRE

DESCRIPTION: