



Material

- Item① Terminal cover : Thermoplastic (UL94V-0)
- Item② Terminal body : Thermoplastic (UL94V-0)
- Item③ Terminal screw : Steel , Zinc plating "-" slot type
- Item④ Wire guard solder pin : Brass, Tin plated
- Item⑤ Clamp :Brass, Ni plated

Electrical

- Voltage rating: 300VAC
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 12-22
- Stranded wire(AWG): 12-22
- Torque(Lb-In): 3.5
- Screw: M2.5
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec

TBH100-D15-xx-LF
LEADFREE

RoHS Compliant

Poles	02	03	04	05	06	07	08	09	10	11	12
Dim L	15.00	25.00	35.00	45.00	55.00	65.00	75.00	85.00	95.00	105.0	115.0
Dim B	10.00	20.00	30.00	40.00	50.00	60.00	70.00	80.00	90.00	100.0	110.0
TOL	±0.15		±0.25		±0.30			±0.40			



煜倫股份有限公司

PART NO. TBH100-D15-xx		CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION:			
DWG NO. TBH100-D15-xx		DRAWING BY						
FILE NO.		PROJECTION		AREA	REVISIONS	HK	DATE	
UNIT / mm	SCALE 1:1							