



SECTION A-A

Material

- Item 1 Insulating body Thermoplastic (UL94V-0)
 - Item 2 Insulating cover Thermoplastic (UL94V-0)
 - Item 3 Terminal screw Steel Cr3+ Zinc plating "-" slot
 - type
 - Item 4 Terminal body(house) Brass, Ni plated
 - Item 5 Contact PIN PhBz (CuSn) Gold plated
- Electrical cULus / IEC

- Voltage rating: 600VAC / 1000VAC
- Current rating: 55A / 276A
- Solid wire: 6-20 / 0.5-16mm
- Stranded wire: 6-20 / 0.5-16mm
- Torque: 18 Lb-In / 1.2 N.m
- Screw: M4.5
- Wire strip length: 13-14mm
- Withstanding Voltage: 2.2KV / 8KV
- Operating temperature: -40°C to +115°C

Poles	02	03	04	05	06	07	08	09	10	11	12
Dim L	23.36	33.52	43.68	53.84	64.00	74.16	84.32	94.48	104.64	114.80	124.96
Dim B	10.16	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76
TOL	±0.25						±0.35				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

TBH101-PWC-xx-LF

SERIES

LEADFREE

02-12WAY

CAGE

90°SMT

MALE

DESCRIPTION: