



N = Number of poles
 Dim.L = $N \times 3.5 + 0.35$
 Dim.P = $(N - 1) \times 3.5$

Poles	Dim.	Dim.L	Dim.P
2-6p		± 0.25	± 0.20
7-12p		± 0.30	± 0.25
13-16p		± 0.35	± 0.30

Materials

- ⚠ Item Ⓔ Terminal body: High temp. polyamide (UL94V-0)
- Item Ⓔ Terminal screw: Steel Zinc plating "+/-" slot type
- Item Ⓒ Wire guard: Stainless steel
- Item Ⓓ Terminal: Brass (CuZn) Tin Plated
- Item Ⓕ Terminal Cover: High temp. polyamide (UL94V-0)

Electrical UL

- Voltage rating: 150VAC
- Current rating: 10A
- Wire range:
- Solid wire (AWG): 16-26
- Stranded wire (AWG): 16-26
- Torque (Lb-In): 2.0
- Screw: M2.0
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.6KV
- ⚠ Operating temperature: -45°C to +65°C
- Soldering temperature: 280°C/10 Sec
- Safety Approval:
- Critical dimension: ▽

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ± 0.50

.X, ± 0.30

.XX, ± 0.10

.XXX, ±

ANG ± 1°

P PROJECTION

照片框

ORDER INFORMATION

TBN035-V11XC-xx-LF

SERIES | LEADFREE
 | 02-16WAY
 | CAP
 | NON POST
 | HIGH 10.6mm
 | 180°SMT

DESCRIPTION: