



Pitch : 5.00mm (0.197inch)

Poles	A(mm)	A(inch)	Poles	A(mm)	A(inch)
2	10.00	0.394	14	70.00	2.756
3	15.00	0.591	15	75.00	2.953
4	20.00	0.787	16	80.00	3.150
5	25.00	0.984	17	85.00	3.346
6	30.00	1.181	18	90.00	3.543
7	35.00	1.378	19	95.00	3.740
8	40.00	1.575	20	100.00	3.937
9	45.00	1.772	21	105.00	4.134
10	50.00	1.969	22	110.00	4.331
11	55.00	2.165	23	115.00	4.528
12	60.00	2.362	24	120.00	4.724
13	65.00	2.559	25	125.00	4.921

Current rating : 16Amp 300V
 Insulation withstands volt : AC2000V min
 Insulation resistance : >2000MΩ DC500V
 Operation temperature : -40°C to +105°C
 Wire range : 12~26 AWG
 Wire strip length : 4~5 mm
 Screw torque : 4.0 lb-inch

	Material	Plating/Finish	Remark
1	Insulating body	Polyamide 66(UL94V-0)	Blue
2	Terminal	Brass	Tin plated
3	Wire protectoc	Phosphor bronze	Tin plated
4	Screw	Steel	Zinc plated
5			

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION

照片框

ORDER INFORMATION

TBN050-D10-xx-LF

SERIES

LEADFREE

02-25WAY

HIGH 10.0mm

DIP180°

DESCRIPTION: