

SECTION A-A

- NOTES: ⁴ 300V 26A Factory wire ⁴ 300V 20A Field wire (IEC 750V 24A)
 1. Rating: ~~300V 26A (IEC 250V 16A)~~
 PITCH: 7.50 mm
 2. Insulation Withstands Voltage:
 AC 2000V/MIN
 3. Insulation Resistance:
 500MΩ or more at DC500V
 4. Using Temperature Range:
 -40°C~+130°C
 5. Screw Torque Value: 5kg-cm
 6. Suitable Electric Wire: AWG 22~12 (IEC 2.5mm²)
 7. Undimensioned Tolerances:

—	∩	□	0.05/10
⊥	//	≡	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONED TOLERANCES			±0.3

⁵ 8. RoHS Compliance

7	SCREW	P	STEEL	M2.5/Zn Plated
6	WIRE CAGE	P	STEEL	Zn Plated
5	SOLDER PIN	P	COPPER	Tin Plated
4	CAM	P	STEEL	Zn Plated
3	END COVER	1	PBT(G15)	GREEN
2	CENTER PIECE	P-1	PBT(G15)	GREEN
1	HOUSING	P	PBT(G15)	GREEN
ITEM	NAME OF PART	Q'TY	MATERIAL	NOTES

TBN075-R18-xx-LF
 LEADFREE
 RoHS Compliant

MORETHANALL
 CONNECTORS
 ASSEMBLIES

煜倫股份有限公司

PART NO. TBN075-R18-xx

DWG NO. TBN075-R18-xx

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
 .XX ± 0.1
 .XXX ±
 AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE