



NOTES:

1. Rating: UL 600V 18 A
IEC 800V 24A
2. Insulation Withstands Voltage:
AC 2500V at 1 minute
3. Insulation Resistance:
500MΩ or more at DC500V
4. Using Temperature Range:
-40°C~+105°C
6. Suitable Electric Wire: AWG 30~12
(0.2~2.5mm²)
7. RoHS compliance

Normal Geometric Tolerancing					
—		//	≡	⊥	
0 to 100	0.2			0 to 10	0.2
over 100 to 150	0.3		0.3	over 10	0.3
over 150	0.5				
Total Pitch Tolerances			Normal dimension Tolerances		
0<U<=30	±0.20		0~30	±0.25	
30<U<=53	±0.25		over 30~53	±0.30	
53<U<=70	±0.30		over 53~70	±0.35	
70<U<=90	±0.35		over 70~90	±0.44	

ITEM	NAME OF PART	MATERIAL	NOTES
3	CONDUCTOR	COPPER-ALLOY	Tin Plated
2	CAGE CLAMP	SPRING STEEL	
1	HOUSING	PA66	UL94-V0 GREY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X. ± 0.30

.X ± 0.30

.XX ± 0.20

.XXX ± 0.10

ANG ± 1°

PPOJECTION

照片框

ORDER INFORMATION

TBR051-W36-01-LF

SERIES

LEADFREE

01 WAY

HIGH 36.50mm

SCREW WIRE

DESCRIPTION: