



	CUL	IEC
Rated voltage	600V	800V
Rated current	30A	32A
Solid wire	22-10AWG	0.5-4mm ²
Stranded wire	22-10AWG	0.5-4mm ²
Impulse withstand voltage	6KV	
Torque(Terminal Screw)	0.7Nm (6in-lbs)	
Terminal Screw	M3	
Wire strip length	8-10mm	
Mounting DIN rail	TS35-7.5/TS35-15	

CONFIRMED & ACCEPTED BY _____

	Material	Plating/Finish	Remark
1	Insulating body	PA66 (UL94 V-0)	
2	Terminal Screw	Steel M3	Zinc
3	Terminal 1	Phosphor bronze	Tin plated
4	Terminal 2	Phosphor bronze	Tin plated
5	Cage clamp	Steel	Zinc

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION 

照片框

ORDER INFORMATION

TBR060-W62-01-LF

SERIES

LEADFREE

01 WAY

HIGH 62.70mm

SCREW WIRE

DESCRIPTION: