



NOTES:

1. Rating: UL 600V 70A
IEC 1000V 76A
2. Insulation Withstands Voltage:
AC 2000V at 1 minute
3. Insulation Resistance:
500MΩ or more at DC1000V
4. Using Temperature Range:
-40°C~+105°C
5. Screw Torque Value: 35kgf-cm
6. Suitable Electric Wire: AWG 14~6
(IEC 16mm²)
7. RoHS Compliance

4	SCREW	STEEL	M5/Zn Plated
3	WIRE CAGE	STEEL	Zn Plated
2	CONDUCTOR	COPPER ALLOY	Tin Plated
1	HOUSING	PA66	UL94-V0 GREY
ITEM	NAME OF PART	MATERIAL	NOTES

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

TBR120-W-01-LF

SERIES

LEADFREE

01 WAY

SCREW WIRE

DESCRIPTION: