



Wire Protector

NO POSN	DIM A
2	16.6 ± 0.3
3	26.6 ± 0.5
4	36.6 ± 0.5
5	46.8 ± 0.7
6	56.8 ± 0.7
7	66.9 ± 0.7
8	77.2 ± 1.0
9	87.2 ± 1.0
10	97.4 ± 1.0
11	107.4 ± 1.5
12	118.0 ± 1.5

ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.2mm 00.= ±0.4mm

Housing Material : Polyamide 66 (PA66), Nature flame-retardant to UL 94V-0

Voltage : 300V (UL), 450V (VDE)

Current : 30A (UL), 32A (VDE)

Working Temperature : T140(IEC), 105° C(UL)

Insert : Brass, nickel-plated

Wire Protector : Stainless spring steel

Screws : M3.0x6, Steel zinc-plated

Wire Range : 1.0 ~ 4.0mm², #22 ~ #10 Sol/#22 ~ #12 Str

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

TBT100-WBP-xx-LF

SERIES

LEADFREE
02~12WAY
WIRE PROTECTOR
BASE
WIRE TO WIRE

DESCRIPTION: